


VE XO X-POT Compact Specification Sheet

Product / Model	X-POT Series/Compact	Art. Code	
Description	Side Stream Filtration and Dosing Unit	Date	
Customer			
Project			
Reference			




Mounting: Wall/Bracket Mounted
Dosing Capacity: 1.18 US Gal
Design Standard: ASME BPVC VIII Div.1

Testing and Quality Assurance

Test Pressure: 225 PSI
Test Medium: Air
Test Certificate: Yes
Drawing: Yes
Design Compliance: ASME U Stamp
Notified Body Inspection: Yes
Warranty: 10 Years
Industry Peer Reviewed Energy Savings: Yes

Construction Materials

Vessel Body/Lid: SS 304
Baffle Plate: SS 316
Magnet Grate: SS 316
Magnets (4no.): Neodymium Rare Earth (Encased in SS 304)
Cartridge Filter: Polypropylene Spun Bonded Fibre
Isolation Valves: SS 304
AAV: DZR Brass (CW602N) (Female)
NRV: SS 304
Fittings: SS 304



Dimensions

Overall Height: 24.80"
Overall Depth: 12.79"
Overall Width: 11.22"

Connections

Isolation Valve: 1/2" NPTF
AAV: 1/2" NPTF

Volume & Weight

Volume: 1.17 US Gal
Dry Weight: 38.00 Pounds
Operational Weight: 51.00 Pounds

Accessories

Pressure Differential Monitoring: PD-Monitor (Optional)
Insulation Jacket: Yes (Optional)

VEXO X-POT Compact Specification Sheet

General Description

A – The VEXO™ X-POT Compact™ assists in the restoration of water quality and flow rates within Hydronic Heating and Cooling Systems to remain reliable and run at their intended design capabilities, by keeping the thermal fluid within the system filtered, clean and free from suspended particulates and micro-bubbles. This also allows Chemical Inhibitor's and Biocides to remain effective, thus reducing the accumulation of Corrosion, Scale and Bio-film deposits which would otherwise cause flow loss, degradation of plant and pipeline material, as well as reduced system reliability, increased running and reactive maintenance costs, water losses and reduced lifespan of system components, X-POT has valid peer reviewed white papers - detailing potential energy savings.

This is achieved by a combination of functions, as the X-POT™ acts as an all-in-one:

- Dirt & Air Separator
- Magnetic Filter
- Side Stream Filter (down to 0.5 micron)
- Shot Feeder (For adding Water Treatment Chemicals)

B – This section specifies cleaning and treatment of circulating HVAC water systems, including the following:

- I. Closed Loop Cooling Systems
- II. Closed Loop Heating Systems

Product Description - Side Stream Water Filtration and Treatment Device

A – The Contractor shall furnish and install a full side stream filtration device that incorporates an industry peer reviewed 'all-in-one', shot feeder, magnetic filter and air and dirt separation device as shown and detailed on the contract documents. The product provided shall be the VEXO™ X-POT Compact™ manufactured by VEXO International (www.vexo.com/us) and exclusively supplied by Skidmore of Benton Harbor, MI or an approved substitution.

B - The product shall be all stainless steel construction including all valves and fittings. Maximum working pressure shall be 150psi with flow rates up to 6.3 GPM with a temperature range of 32°F to 200°F. Dosing capacity shall be a minimum of 1.1 Gallons and Cartridge Filtration range to be no less than 50µ to 0.5µ (bag filters are not acceptable). Magnetic filtration shall consist of no less than four (4) rare earth magnets - four (4) with a minimum of 26.5 lbs pull force each - designed for easy removal and cleaning. Air separation efficiency to be 100% removal to micro-bubble level and incorporate an automatic air vent. Total system volume capacity shall be no less than 9,130 Gallons. The product must be provided with 1/2" isolation and drain valves and have an option for an insulation jacket with filter PD condition alarm installed to notify of timely filter changes and alert to water quality.