



X-POT6+®

X-POTXP+®

2 YEAR WARRANTY

The warranty certificate for this X-POT is valid for a period of 2 years (24 months) from the date of installation.

This warranty covers the repair or replacement of the unit at our discretion.

DOS - Date Of Supply DD MM YY

DOI - Date Of Installation DD MM YY

Warranty - What is covered?

The VEXO International (UK) Ltd warranty for this BOSS™ X-POT® covers manufacturing defects, under our standard terms and conditions of sale.

If the unit is identified with a manufacturing defect then no charge is made for correcting the defect.

The BOSS X-POT + Skid Units are made to order & are marked with a unique traceable serial number located on the front of the X-POT Vessel. **(Remove insulation jacket to view)**

Model Type: X-POT6+ X-POT XP+

Serial Number: **AS INDICATED ON UNIT**

Warranty - What is not covered?

- If a problem has arisen as a direct result of the connected system, misuse, incorrect handling, incorrect installation or incorrect commissioning, maintenance and/or use of non-manufacturer made parts and/or filters.
- If a manufacturing defect is identified, additional remedial works as a result of misuse, incorrect handling, incorrect installation or incorrect commissioning then the additional work is chargeable.
- Installation costs and consequential losses are not covered by this warranty.

Complete all relevant sections accurately - issue to the O&M manual responsible representative.



X-POT6+®

X-POTXP+®

DECLARATION OF CONFORMITY

Manufacturer	Distributor
Vexo International (UK) Ltd.	BSS Industrial
6 The Granary Buildings, Millow Hall Farm Millow (Nr Dunton), Biggleswade Bedfordshire SG18 8RH.	



For and on behalf of
Vexo International (UK) Limited

Darren Wilkinson, Managing Director

6 The Granary Building
Millow Hall Farm, Millow (Nr Dunton)
Biggleswade, Bedfordshire
SG18 8RH

+44 (0) 1767 500 150

Registered in England & Wales No: 7205096

Range Name:

X-POT6+® (up to 60L/min)
X-POT XP+® (up to 210L/min)

Operating Conditions

Working Pressure Range
X-POT6+® - **Min: 0 Bar - Max: 10 Bar**
X-POT XP+® - **Min: 0 Bar - Max: 16 Bar**

0°C Minimum Working Temperature - +95°C Maximum Working Temperature

Additional Information

IP44 Protection Rating

All appropriate components CE/UKCA marked prior to assembly, and are bound by their individual applicable directives including but not limited to:

Pressure Equipment Directive

2014/68/EU

Low Voltage Directive

2014/35/EU

Electromagnetic Compatibility Directive

2004/108/EC

Machinery Directive

2006/42/EC