

## Product Data Sheet

### X-PO45

#### General Description

A pre-commission cleanser

#### Properties

A blend of cleaning and dispersing agents.  
Removes oils, greases and flux residues from new installations.

#### Benefits

Neutral pH.  
Non-aggressive.  
High dispersing power.

#### Use Instructions

**Normal Dose Rate:** To a typical central heating system (70l) dose 250mls.  
**Instructions:** Use in new installations.  
Circulate for a minimum of 24 hours.  
For best results a good flow rate is required.

#### Technical Data

**Composition:** An aqueous solution of chelant, polymers and surfactants.  
**Appearance:** Colourless  
**Sg (at 20C):** 1.032  
**pH:** 5.5-6.5

#### Handling and Storage

Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.  
Store in a cool, well ventilated area.  
Keep container tightly closed.  
For full guidance on health and safety matters consult the Safety Data Sheet (SDS)  
Carry out a 'Control Of Substances Hazardous to Health' (COSHH) assessment before use.

#### Product Compatibility

Compatible with most closed circuit water treatment products.

#### Test Methods

**Laboratory:** No test method available.  
**Site:** No test method available.

#### Disposal Method

**Empty Bottles:** As per product SDS. VEXO offer a takeback scheme on empty bottles - please contact VEXO for a quote.